



A24 Industrial Telephone & Headset

Technical Specifications

<i>Storage Temperature:</i>	-40°C ----- 70°C
<i>Operating Temperature:</i>	-20°C ----- 55°C
<i>Relative Humidity:</i>	max 95%
<i>Case Protection:</i>	IP 66
<i>Dialing Mode Selection:</i>	DTMF or Pulse
<i>CE-Conformity:</i>	EN 50081, EN 50082, EN 60950 line approach according CTR21+
<i>Loudness Level:</i>	60dB(A) - 90dB(A) in 1m distance
<i>Functions:</i>	per push buttons 4 - 6 functions, mute, memory dialing, receiver amplification+6dB, headset, line ground/flash, 4 speed dialing numbers, open listening, short dialing
<i>Connection Terminals:</i>	clamping range 0,08 - 2,5 mm single, multi and fine wire
<i>Glands:</i>	M16, Ø 5 - 10 mm dummy plug: 1 x M12, 1 x M16 handset: M12Flex, Ø 3 - 6,5 mm
<i>Material:</i>	case: polyamide locking screw: V4A (1.441)



<i>Dimensions:</i>	Height 221 mm Width 154 mm Depth 105 mm
<i>Distance between Holes for Attachment:</i>	128 - 134 mm
<i>Weight:</i>	ca. 1250 g

