



VHF MARINE TRANSCEIVER

IC-M73

Slim, Stylish, Powerful VHF with Professional Features



Last Call Voice Recording

The last call voice recording function automatically saves the last incoming call for 1 minute. You can also start recording manually. You will not miss an important call.



Active Noise Cancelling Technology

The built-in bidirectional active noise cancelling reduces background noise to up to 90% and improves both your transmitted voice and incoming call. You will hear better and clearer!



Bass Boost Function

The signal processing technology emphasizes low-pitched sound to provide a rich bass sound for both transmit and receive signals.



700mW Loud Audio



6W RF Output Power



IPX8 Submersible Plus™ Waterproofing

700mW Loud Audio

The IC-M73 uses a BTL (bridge-tied load) amplifier that doubles the audio output. Its internal speaker delivers a loud 700mW audio output with clear sound.

6W RF Output Power

The IC-M73's 6 Watts of transmit power will provide extended communication range for the user. A large capacity Lithium-Ion battery allows for 16 hours of operation, under normal conditions*. * Typical operation with 5:5:90 duty ratio. 18 hours for basic version.

SPECIFICATIONS

GENERAL		
Frequency range	Tx	156.025–157.425MHz
	Rx	156.050–163.275MHz
Usable channel groups	INT, USA, CAN, WX channels	
Type of emission	16K0G3E (FM)	
Current drain (at 7.4V DC)		
Tx 6W output	1.5A	
Rx Max. audio (Int SP/Ext SP)	450mA/250mA	
Operating temp. range	–20°C to +60°C; –4°F to +140°F	
Antenna impedance	50Ω	
Dimensions (WxHxD)	52.5x125x30 mm	
(projections not included)	2.07x4.92x1.18 in	
Weight (approx.)	320g; 11.3oz	
	(With BP-245N, FA-S64V, MB-103)	

Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.

IPX8 Submersible Plus™

The IC-M73 continues to offer Icom's best waterproof protection. The radio has been tested to survive after being submersed in 1.5m (4.9ft) depth of water for 30 minutes.

**Slim, Hourglass Body
Wide Viewing Angle LCD**

The IC-M73 has a stylish, ergonomic design. A durable and rugged body provides for user-friendly operation and long life. A wide viewing angle, high intensity LCD offers bright, easy to read characters.

TRANSMITTER	
Output power (Hi/Mid/Low)	6W/3W/1W
Max. frequency deviation	±5.0kHz
Frequency stability	±10ppm
Spurious emissions	–68dBc typ.
Adjacent channel power	70dB
Audio harmonic distortion	Less than 10% (at 60% dev.)
Residual modulation	40dB
RECEIVER	
Sensitivity	0.22μV typ. (at 12dB SINAD)
Squelch sensitivity	0.35μV typ. (at threshold)
Adjacent channel selectivity	70dB typ.
Spurious response	70dB typ.
Intermodulation	70dB typ.
Hum and noise	40dB
Audio output power	700mW typ. (Internal SP)
(at 10% distortion, 8Ω load)	350mW typ. (External SP)

Additional features

- AquaQuake™ water draining function
- Dual/Tri-Watch function for monitoring Channel 16 and/or call channel
- 4 level battery indicator
- Favorite channel and tag scan functions
- Rapid desktop charger, BC-210, and cigarette lighter cable, CP-25H, are supplied
- Optional waterproof speaker-microphones, HM-167 and HM-202
- Auto power save function
- Basic version (no voice recorder, no noise canceller and no bass boost function) available for limited markets.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Applicable IP Rating

Ingress Protection Standard	
Water	IPX8 (Waterproof protection)

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

BATTERY PACK

BP-245N Li-Ion 7.4V,
1900mAh (min.), 2000mAh (typ.).

RAPID CHARGER

Charges the BP-245N in 2.5 hours (approx.).
* BC-123SA for 120V AC. SE for 230V AC.

MULTI-CHARGER

Charges up to six BP-245N in 2.5 hours (approx.).
AD-129 is supplied with the BC-197, depending on version.

Supplied Accessories:


- Cigarette lighter cable, CP-25H
- AC adapter, BC-123SA/SE*
- Rapid charger, BC-210
- Battery pack, BP-245N
- Belt clip, MB-103
- Antenna, FA-S64V
- Hand strap
- * May differ depending on version.

SPEAKER-MICROPHONES

HM-167 IPX8 rugged type
HM-202 IPX7 compact type

BELT CLIPS

MB-86 Swivel type
MB-103 Alligator type

LEATHER BELT HANGERS

MB-96N Swivel type
MB-96F Fixed type

CIGARETTE LIGHTER CABLE & DC POWER CABLES

CP-25H For use with BC-210
OPC-515L For use with BC-210
OPC-656 For use with BC-197

ANTENNA

FA-S64V

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia, Japan and/or other countries. AQUAQUAKE and SUBMERSIBLE PLUS are trademarks of Icom Inc. (Japan). All other trademarks are the properties of their respective holders.

Icom Inc.

1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!**Icom America Inc.**

2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom Brazil

Rua Pernambuco, 353 - Sala 901
Belo Horizonte, M.G.
30130-150, Brazil
Phone: +55 (31) 3582 8847
Fax: +55 (31) 3582 8987
E-mail: sales@icombrasil.com

Icom (Europe) GmbH

Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone: +49 (6196) 76685-0
Fax: +49 (6196) 76685-50
E-mail: info@icom-europe.com
URL: <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom Polska

81-850 Sopot, ul. 3 Maja 54, Poland
Phone: +48 (58) 550 7135
Fax: +48 (58) 551 0484
E-mail: icompolksa@icompolksa.pl
URL: <http://www.icompolksa.com.pl>

Icom (UK) Ltd.

Blacksole House, Altira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone: +44 (0) 1227 741741
Fax: +44 (0) 1227 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom France s.a.s.

Zac de la Plaine,
1 Rue Brindejonc des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Icom New Zealand

146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Your local distributor/dealer: